

Robust
Flexible

Modular





CENTRE GLAZED

Popular and flexible, the COMMERCE Centre Glazed System will meet all general wind load/span requirements.

Ideal for SHOPFRONT applications and available in 101.6mm and 150mm widths, the COMMERCE Centre Glazed System is suitable for glass thicknesses from 5mm up to 12.38mm.

The Strong extruded profiles mean spans up to 3 metres can be easily achieved.

Self Draining Sills and Transom designs optimise weatherability and maximise water management.

The COMMERCE Architectural Systems range has been designed with a modular theme in mind allowing for the incorporation of other EZIAL Framing suites, doors and windows and can be complimented with a range of louvres and infill panels.

ROBUST

FRONT GLAZED

When the design calls for a glass facade, the **COMMERCE** Front Glazed System is the answer.

The system is suitable for Low to High Rise Curtain Wall applications and is also extensively used for Sloping Atrium applications.

Available in 100mm and 150mm Frame Widths.

The Double Glazed System provides good sound insulation reducing outside noise levels and minimises the use of heating and cooling appliances, saving money on energy bills.

A simple square cut system with aesthetic appeal, clean lines which accommodates Glass Thicknesses from 5mm up to 12.38mm in Single Glazed and from 21mm to 28mm Insulated Glass Units in Double Glazed.

The system takes advantage of other **EZIAL** suites, doors and windows and can be complimented with a range of louvres and infill panels.

FLEXIBLE





45mm COMMERCIAL DOOR

Designed for the fabrication of Glazed Entrance Doors for Shopfronts, Offices, general Commercial, Industrial Projects and Residential applications.

Suitable for Hinged, Pivot or Sliding configurations.

Sliding Options to suit Top Hung or Bottom Rolling manually operated sliding doors.

Automatic Operator Sliding Door applications are one of the more popular installations suited to the COMMERCE 45mm Commercial Door System.

Flush pocket glazing means no vertical glazing beads with horizontal beads on one side only, resulting in improved appearance, security and lower manufacturing costs.

Suitable for a range of glass thicknesses from 5mm up to 12.38mm in single glazed and 22mm to 30mm Insulated Glass Units in Double Glazed.

VERSATILE